

SEALED HOLLOW INSULATING MODULE

ASP- INS



Product Specification ASP- INS

Module Dimension		Weight
L1200*W600*D31mm		27.4kg
Specification	ASP-INS	
Thermal Conductivity	$\geq 1.2\text{W/mK}$	
Nominal Power (Pm)	48W	64W
Open Circuit Voltage (Voc)	116V	116V
Short Circuit Current (Isc)	0.59A	0.78A
Voltage at Max. Power(Vm)	87V	87V
Current at Max. Power (Im)	0.55A	0.74A
Transparency	40%	20%

Transparency and pattern can be customized
 Tested under STC:1000W/m², AM1.5, 25°C

PV Tile

ASP-SST



Product Specification ASP- SST

Module Dimension		Weight
L1275*W420*D42mm		9kg
L1275*W720*D42mm		16kg
Specification	ASP-SST-40	ASP-SST-85
Nominal Power (Pm)	40W	85W
Open Circuit Voltage (Voc)	119.6V	120.5V
Short Circuit Current (Isc)	0.48A	1.04A
Voltage at Max. Power(Vm)	94.7V	94.5V
Current at Max. Power (Im)	0.42A	0.90A

Tested under STC:1000W/m², AM1.5, 25°C

SHAPED MODULE

ASP-SSP

