

PWSOLAR 10W POLYCRYSTALLINE MODULE

ADVANCED PERFORMANCE & PROVEN ADVANTAGES



- ◆ High module conversion efficiency up to 10.74% by using innovative Half-cell design and Multi-busbar(MBB) cell technology.
- ◆ Low temperature coefficient and excellent performance under high temperature and low light conditions.
- ◆ Robust aluminum frame ensures the modules to withstand wind loads up to 2400Pa and snow loads up to 5400Pa.
- ◆ High reliability against extreme environmental conditions (passing salt mist, ammonia and hail tests).
- ◆ Potential induced degradation (PID) resistance.
- ◆ Positive power tolerance of 0 ~ +5w.

ELECTRICAL CHARACTERISTICS AT STC

Model	PW10Wp-36P
Maximum Power (P_{max})	10W
Power Tolerance	0 ~ + 5W
Open Circuit Voltage (VOC)	21.60V
Short Circuit Current (ISC)	0.72A
Voltage at Nominal Power (V_{mp})	18.00V
Current at Nominal Power (I_{mp})	0.60A
Size of Module	365 x 255 x 17mm
Standard Test condition	Irradiance:1000W/M2 Temp: 25°C , & AM :1.5G spectrum
Maximum system voltage	800V DC
Operating temperature	- 40°C to +85°C
Module Efficiency	10.74%

ELECTRICAL CHARACTERISTICS AT STC

NOCT	45 +/- 2°C
Voltage temperature coefficient(V_{oc})	-0.33%/°C
Current temperature coefficient (I_{sc})	+0.058%/°C
Power temperature coefficient(P_{mpp})	-0.400%/°C
Minimum power tolerance	+/-10%
NOCT	45 +/- 2°C



MECHANICAL CHARACTERISTICS

Cell Type	Polycrystalline
Number of cell	36pcs (4 x 9)
Size of Module	365 x 255 x 17mm
Weight	About 1.00kgs
Front Cover	3.2mm tempered glass with AR coating
Frame	Anodized aluminum alloy
Junction Box	IP65, 3 diodes
Cable	TBA
Connector	TBA

MODULE WARRANTY

25-year limited warranty of 80% power output; 10-year limited warranty of 90% power output; 5-year limited warranty of materials and workmanship.

PACKING



Standarding Packing: 500pcs/Pallet

Module Quantity of 20' container: 15000pcs

Module Quantity of 40' container: 22000pcs

ENGINEERING DRAWING

IV CURVES



Room 101, No. 5 Building, No. 9 Haikou Road, Shinan District, Qingdao, China 266000

0086 532 85872070

0086 155 6392 6558 WhatsApp 0086 138 6421 6496

sales@pwsolarpower.com

info@pwsolarpower.com

www.pwsolarpower.com

Specifications in this datasheet are subject to change without prior notice